

TECHNICAL DATA SHEET

Document: ST 309 Edition: 02

Date: January 2025



Commercial name

PROPALOGGER USB TEMP & RH SINGLE USE LCD

Company identification

Producer: PROPAGROUP S.p.A.

Address: Via Genova, 5/B - 10098 RIVOLI (Turin) - Italy

www.propagroup.com - export@propagroup.com Ph. +39 011 9507788 Fax +39 011 9507808

1. Description and application

PROPALOGGER USB TEMP & RH SINGLE USE LCD is a simple single-use portable device with LCD screen specially designed for cold chain. This product is mainly used to monitor and record the temperature and humidity data of food, medicine, chemical products, and other products in the process of storage and transportation. It is widely used in all aspects of warehouse storage and logistics cold chain, such as refrigerated containers, refrigerated vehicles, refrigerated distribution boxes, Cold storage, laboratory, etc. Data reading and parameter configuration can be realized through USB interface (which can be configured before use). After inserting, the report can be generated conveniently and automatically, and no driver needed to be installed when inserting into the computer.



2. Technical characteristics

| Key Operating Specifications | |
|------------------------------|--|
| Battery shelf life | Typically 2 years |
| Dimension | 95,5 x 49 x 7,8 mm |
| Weight | 25 g |
| Connectivity | USB 2.0 |
| Detecting Temperature Range | Between -30 °C and +70 °C |
| Detecting Humidity Range | Between 0 % and 90 % |
| Temperature Accuracy | ±0,5 °C between -20 °C and +40 °C ±1,0 °C other range |
| Humidity Accuracy | ±5 % between 10 % and 90 % |



TECHNICAL DATA SHEET

Document: ST 309

Edition: 02

Date: January 2025

PROPALOGGER USB TEMP & RH SINGLE USE LCD



| Humidity Resolution | 0,1 % |
|------------------------|---|
| Temperature Resolution | 0,1 °C |
| Data Storage Capacity | 32.000 |
| In-use life | Up to 220 days |
| Start Mode | Push-To-Start or Timing Start |
| Logging Interval | Programmable 10s - 18h Default 10mins |
| Alarm Range | User configurable |
| Alarm Delay | User configurable 0-254 mins |
| Report Generation | Automatic PDF/CSV Report Generation |
| Software | Temp (RH) Management Software (For Windows,21 CFR 11 Compliant) |
| Protection Grade | IP54 |
| Certifications | FCC, CE, RoHS |
| Operating system | Windows 7 or higher Microsoft .NET Framework 4.0 or higher Visual C++ |

3. Production and Quality

PROPAGROUP is UNI EN ISO9001 / ISO14001 certified and produces in accordance with the requirements of the main European and international standards in the sector.

The values indicated here are the result of standardised lab tests and meant only as an indication to help select and use the products. The user is responsible for ensuring the suitability and completeness of such information in relation to how the product is to be used.

Written by: Technical Management Revised by: Quality Department Approved by: Management